2	TiTle or b	4 ~	claimed.	i ~ .
<i>Z</i> .	wnat	LS	статшец.	LS:

- Claim 1. A precise linear fastener system comprising:
- 4 a collet member having a base end, a top end, an inner
- 5 engaging surface, and an outer ribbed surface positioned about
- 6 a central axis;
- 7 a compression ring member having a base end, a front end,
- 8 an inner ribbed surface, and an outer surface positioned about
- 9 a central axis;
- 10 said inner ribbed surface of said compression ring member
- 11 being constructed and arranged for coaxial alignment and
- 12 overlapping engagement with respect to said outer ribbed
- 13 surface of said collet member, said compression ring member
- 14 linearly traversable with respect to said outer ribbed surface
- of said collet member between a first release position and a
- 16 second engaged position, wherein said engaged position results
- in said ribbed surfaces compressing said collet member and
- 18 tensilely loading said compression ring member to engage a
- 19 shank member having an outer gripping surface, and wherein said
- 20 release position results in expansion of said collet member
- 21 thereby releasing said outer gripping surface of said shank
- 22 member.

23

- Claim 2. The precise linear fastener system of claim 1
- 25 including

a shank member having an outer gripping surface, a first end,

2 and a second end.

3

Claim 3. The precise linear fastener system of claim 1 4 wherein said ribbed outer surface of said collet member 5 includes at least one outwardly and circumferentially extending 6 rib, each said rib including a first ramp surface to facilitate 7 coaxially aligned linear overlapping 8 movement of 9 compression ring in relation to said collet member for engagement thereof, and a second ramp surface to facilitate 10 11 linear removal of said compression ring from said collet

12 member.

13...

15

16

14 ... Claim 4. The precise linear fastener system of claim 1 wherein said inner engaging surface of said collet member is constructed and arranged with a conjugate shape in relation to said outer gripping surface of said shank member.

18

19

20

21

17

Claim 5. The precise linear fastener system of claim 1 wherein said inner engaging surface of said collet member is constructed and arranged with internal threads.

22

23

24

25

Claim 6. The precise linear fastener system of claim 1 wherein said inner engaging surface of said collet member is constructed and arranged with a knurled surface.

26

Claim 7. The precise linear fastener system of claim 1 wherein said inner engaging surface of said collet member is constructed and arranged with a generally smooth surface.

Claim 8. The precise linear fastener system of claim 1 wherein said inner engaging surface of said collet member is constructed and arranged with at least one inwardly depending lip; wherein said inwardly depending lip is constructed and arranged with at least one tapered surface for cooperation with a conjugate tapered surface on said outer gripping surface of said shank member;

wherein linear traversal of said compression ring member with respect to said axially aligned collet member compresses said collet member and tensilely loads said shank member.

Claim 9. The precise linear fastener system of claim 1 wherein said inner engaging surface of said collet member is constructed and arranged with at least one inwardly depending lip, wherein said inwardly depending lip is constructed and arranged for cooperation with at least one snap ring groove in said outer gripping surface of said shank member;

wherein linear traversal of said compression ring member
with respect to said axially aligned collet member compresses
said collet member to engage said at least one snap ring
groove.

Claim 10. The precise linear fastener system of claim 1
wherein said first end of said shank member includes a
tensioning means, said tensioning means being constructed and
arranged to allow said shank member to be tensilely loaded
prior to linear traversal of said compression ring member into
said engagement position with respect to said collet member.

Claim 11. The precise linear fastener system of claim 10 wherein said shank member tensioning means includes at least two generally flat surfaces, wherein said at least two generally flat surfaces are constructed and arranged for gripping and placing a tensile load on said shank member prior to linear traversal of said compression ring member into said engagement position with respect to said collet member.

18 "

Claim 12. The precise linear fastener system of claim 10 wherein said shank member tensioning means includes at least one groove extending around the circumference of said first end of said shank member, wherein said at least one groove is constructed and arranged for gripping and placing a tensile load on said shank member prior to linear traversal of said compression ring member into said engagement position with respect to said collet member.

Claim 13. The precise linear fastener system of claim 10 wherein said shank member tensioning means includes at least one internal bore extending inwardly from said first end of said shank member along the longitudinal centerline of said shank member, wherein said at least one internal bore is constructed and arranged for gripping and placing a tensile load on said shank member prior to linear traversal of said compression ring member into said engagement position with respect to said collet member.

Claim 14. The precise linear fastener system of claim 13
wherein said internal bore includes internal threads.

Claim 15. The precise linear fastener system of claim 13 wherein said internal bore includes at least one axially aligned groove extending around the circumference of said internal bore.

Claim 16. The precise linear fastener system of claim 10 wherein said shank member tensioning means includes a frangible stem, whereby said frangible stem is severed from said first end of said shank member when said first member reaches a predetermined tension prior to linear traversal of said compression ring member into said engagement position with respect to said collet member.

5 6	interfitting relationship in said release position.	
4	constructed and arranged to maintain an axially	aligned
3	said inner ribbed surface of said compression ring me	mber are
2	wherein said outer ribbed surface of said collet me	mber and
1 .	Claim 17. The precise linear fastener system of	claim 1

Claim 18. The precise linear fastener system of claim 1 wherein said outer surface of said compression ring member includes at least two wrench flats for increasing or decreasing the said tension applied to said shank member subsequent to linear traversal of said compression ring member into said engagement position with respect to said collet member.

13

14

12

10:

11

Claim 19. The precise linear fastener system of claim 1 15 wherein said collet member is constructed of plastic.

16

17

18

Claim 20. The precise linear fastener system of claim 1 wherein said collet member is constructed of copper.

19

20 Claim 21. The precise linear fastener system of claim 1 wherein said collet member is constructed of brass. 21

22

23 Claim 22. The precise linear fastener system of claim 1 wherein said collet member is constructed of bronze. 24

25

1	Claim 23. The precise linear fastener system of claim 1
2	wherein said collet member is constructed of aluminum.
3 ·	
4	Claim 24. The precise linear fastener system of claim 1
5	wherein said collet member is constructed of steel.
6	
7	Claim 25. The precise linear fastener system of claim 1
8	wherein said collet member is constructed of rubber.
9	
0	
l 1	
12	